

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)
WILDCAT RC 88 Rubber Cleaner

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name **WILDCAT PRODUCTS INC**

Emergency Telephone Number 817-579-7333

Address (Number, Street, City, State and ZIP Code)

Telephone Number for Information 817-579-7333

300 SADDLEVIEW CT.

Date Prepared 05-19-2016

GRANBURY, TEXAS 76048

Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information DOT HAZARD CLASSIFICATION; FLAMMABLE LIQUID 3

Hazardous Components (Specific Chemical Identity, Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits

Recommended

% (optional)

Light Aliphatic Solvent Naphtha

500

300

CAS#64742-89-8

Section III—Physical/Chemical Characteristics

Boiling Point N/E

Specific Gravity (H₂O-1): 0.79

Vapor Pressure PS-G@70 F

Melting Point N/A

Solubility in water Negligible

Evaporation Rate (=1): N/E

Appearance and odor: colorless liquid with white suspended solids. Naphtha odor

Section IV—Fire and Explosion Hazard Data

Flash Point (Method used) 125F (TCC)

Flammable Limits

%LEL(N/E)%UEL
L/N/E

Extinguishing Media Foam, dry chemical, carbon dioxide Do not use direct water stream

Unusual Fire and Hazards None known

(Reproduce locally)

OSHA 174 Sept.

1985

Section V—Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid) Oxidizing material (mat to avoid): strong oxidizing agents

Hazardous Decomposition products Carbon dioxide, carbon monoxide

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI—Health Hazard Data

Route(s) of Entry	Inhalation?	Skin? X Absorption	Ingestion?
-------------------	-------------	--------------------	------------

Health Hazards (Acute and Chronic) Inhalation: Excessive inhalation of vapors can cause nausea and respiratory irritation, dizziness

Weakness, nausea, headache possible unconsciousness or asphyxiation,

Carcinogenicity	NTP	IARC	OSHA
-----------------	-----	------	------

Signs and Symptoms of Exposure

Medical Conditions
Generally Aggravated by Exposure

Emergency and First Aid Procedures flush with water for 15 minutes for eyes...skin irritation ...wash with soap and water Inhalation remove to fresh air:
Ingestion DO NOT INDUCE VOMITING GET IMMEDIATE ATTENTION

Section VII—Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released contain spill, keep out of surface water and any sewers

Waste Disposal Method dispose in accordance with local and state regulations

Precautions to Be Taken in Handling and Storing store in original container away from open flame in a cool place

Other Precautions

Section VII—Control Measures

Respiratory Protection (Specify Type) as required to prevent over exposure

Ventilation	Local Exhaust explosion proof ventilation is required	Special
	Mechanical (General)	Other

Protective Gloves as required to minimize skin protection Eye Protection safety glasses or goggles

Other Protective Clothing or Equipment

Work/Hygienic Practices